

# Precise Measurement of the Neutron Beta Decay Parameters “*a*” and “*b*”

The *Nab* Collaboration

- Goals, motivation of experiment
- Basic measurement technique and spectrometer design
- Running requirements
- Projected costs and responsibilities
- Projected schedule

FNPBL SNS PRAC Meeting  
Oak Ridge, 8 September 2005

## THE NAB COLLABORATION

<i>Arizona State University</i>	R. Alarcon,
<i>Los Alamos Nat'l. Lab.</i>	<b>J.D. Bowman</b> , S.I. Penttilä, W.S. Wilburn,
<i>Univ. of New Hampshire</i>	J.R. Calarco, F.W. Hersman,
<i>Oak Ridge Nat'l. Lab.</i>	T.V. Cianciolo, K.P. Rykaczewski, G.R. Young,
<i>Univ. of South Carolina</i>	V. Gudkov,
<i>University of Tennessee</i>	G.L. Greene, R.K. Grzywacz,
<i>University of Virginia</i>	M.A. Bychkov, E. Frlež, <b>D. Počanić</b> .

Home page – <http://nab.phys.virginia.edu>

## GOALS OF THE EXPERIMENT

- Measure the electron-neutrino parameter  $a$  with  $\sim 10^{-3}$  accuracy

$$-0.1054 \pm 0.0055 \quad \text{Byrne et al '02}$$

current results:  $-0.1017 \pm 0.0051 \quad \text{Stratowa et al '78}$

$$-0.091 \pm 0.039 \quad \text{Grigorev et al '68}$$

- Measure the Fierz interference term  $b$  with sub-percent accuracy

current results: **none**

## NEUTRON DECAY PARAMETERS (SM)

$$\frac{dw}{dE_e d\Omega_e d\Omega_\nu} \simeq k_e E_e (E_0 - E_e)^2 \times \left[ 1 + a \frac{\vec{k}_e \cdot \vec{k}_\nu}{E_e E_\nu} + b \frac{m}{E_e} + \langle \vec{\sigma}_n \rangle \cdot \left( A \frac{\vec{k}_e}{E_e} + B \frac{\vec{k}_\nu}{E_\nu} + D \frac{\vec{k}_e \times \vec{k}_\nu}{E_e E_\nu} \right) \right]$$

with:


$$a = \frac{1 - |\lambda|^2}{1 + 3|\lambda|^2} \quad A = -2 \frac{|\lambda|^2 + \text{Re}(\lambda)}{1 + 3|\lambda|^2}$$

$$B = 2 \frac{|\lambda|^2 - \text{Re}(\lambda)}{1 + 3|\lambda|^2} \quad D = 2 \frac{\text{Im}(\lambda)}{1 + 3|\lambda|^2}$$

$$\lambda = \frac{G_A}{G_V}$$

( $D \neq 0 \Leftrightarrow T$  invariance violation.)

# PROBLEMS WITH $A$ AND $\lambda$



(from PDG 2005 compilation)

Note: sensitivity of  $a$  to  $\lambda$  comparable to that of  $A$ .

## FURTHER CONSIDERATIONS

- Beta decay parameters constrain L-R symmetric model extensions to the SM. [Herczeg, Prog. Part. Nucl. Phys. **46**, 413 (2001)].
  
- Sensitivity of  $a$  to L-R model parameters such as  $\bar{a}_{RL}$  and  $\bar{a}_{RR}$  competitive and complementary to that of  $A$  and  $B$ . [*ibid*].
  
- Fierz interference term, never measured for the neutron, offers a unique test of non- $(V - A)$  terms in the weak Lagrangian  $(S, T)$ .
  
- A general connections exists between non-SM (e.g.,  $S, T$ ) terms in  $d \rightarrow ue\bar{\nu}$  and limits on  $\nu$  masses. [Ito + Prézeau, PRL **94** (2005)].

## EXPERIMENTAL METHOD

We need to determine dependence of decay rate  $dw$  on  $\cos \theta_{e\nu}$ .

Will measure  $p_p$  (TOF) and  $p_e$  (Si detector);  $\cos \theta_{e\nu}$  follows from


$$p_p^2 = p_e^2 + 2p_e p_\nu \cos \theta_{e\nu} + p_\nu^2.$$

No polarization—no need to worry about spin transport!


Custom spectrometer with  $\vec{B}$  field expansion, no material windows insures:

- hermeticity: near- $4\pi$  sr coverage  $\Rightarrow$  excellent statistical sensitivity (superior to previous measurements of  $a$ , and  $A$ );
- $\cos \theta_{e\nu}$  reconstructed in kinematically complete way;
- $n$ ,  $p$ ,  $e$  interact only with  $\vec{E}$ ,  $\vec{B}$  fields and detectors;
- magnetic field pinch minimizes backscattered electron events;
- imaging of source  $n$  distribution on the face of Si detectors.





## ELECTROMAGNETIC SPECTROMETER




# ELECTROMAGNETIC FIELD PROFILES




# BASIC DESIGN OPTIONS



## TIME OF FLIGHT SPECTRA




electrons



protons


## SIMULATED DATA (GEANT 4)



electrons: red

protons: blue

## $e^-$ REFLECTION AT FIELD PINCH (GEANT 4)





Si thickness: 2 mm





## SI DETECTOR PROTOTYPES (1/10 size)

⇓ front ⇓

back ⇒



## EXPECTED PHYSICS SIGNAL (GEANT 4)



## RUNNING REQUIREMENTS

With SNS operating at 1.4 MW, we expect to record  $2 \times 10^8$  neutron decay events in a standard  $\sim 10$ -day run,  $7 \times 10^5$  s.

Total data sample required will comprise  $\sim 5 \times 10^9$  neutron decays collected during about 6-7 months of production beam time spread over  $\sim 3$  years in several 1-2 month runs.

Statistical uncertainties well under 1% per standard run in both *a* and *b*. Current understanding of systematic errors in agreement with  $10^{-3}$  goal (work is ongoing).

We would like to run both “P” and “PZ” configurations because of their significantly different systematics.

## EQUIPMENT COST ESTIMATE AND RESPONSIBILITIES

1. Superconducting solenoid and HV electrodes (UVa/ <b>NSF</b> )	0.5–1 M\$
design: LANL (analytical), UNH+ASU (Tosca), UVa (Monte Carlo)	
2. Si detectors + readout: (ORNL,UT/ <b>DoE</b> )	
a. Si detectors (design: LANL+UT)	100 k\$
b. waveform digitizer readout+DAQ (design: ORNL+UT)	180 k\$
3. Neutron collimation	30 k\$
4. Vacuum system	30 k\$
5. Supporting mechanical structure	30 k\$
	Total (est.) 1.5 M\$

Additional: \* 250 k\$/yr. LANL R&D funds starting 10/2006;

\* will seek UVa matching funds for spectrometer magnet.

## (AN OPTIMISTIC) SCHEDULE

- 2005 finish conceptual design;
- 2006 1/2: submit proposals to SNS PAC and NSF/DoE for funding;  
2/2: freeze design, prepare purchase orders;
- 2007 (subject to available funding) take delivery of equipment, shake down individual systems, start installing in beam;
- 2008 initiate test runs; routine data taking by year end;
- 2009 more data runs, concurrent analysis;
- 2010 last data runs; data analysis;

## “Other” Questions

Outstanding technical issues that must be resolved?	Detector development (close to completion).
Is beam required to address these issues?	No.
Unusual safety issues?	None.
Radioactive waste generated?	Activated beam windows, stop.
Special environmental requirements?	Low backgrounds, similar to other FNPB experiments.
Backgrounds generated by experiment?	Stray magnetic fields.
Ease of removal, installation?	Straightforward, using a crane.
Staging requirements out of beam?	Floor space elsewhere.
Computing, el. power requirements?	Ordinary.
Average users on site? Students in project?	About 5; ~3 students.
Interactions between <a href="#">Nab</a> and <a href="#">abBA</a> ?	Full synergy.

## More on Interplay of Nab and abBA

Both Nab and abBA use the same Si detectors and DAQ. Nab builds on existing abBA R&D.

Nab will provide abBA with working Si detectors and DAQ.

Electromagnetic spectrometers for the two experiments have different requirements:

- abBA spectrometer is more complex as it has to accommodate polarization and spin transport with precision polarimetry.
- Nab's is a precision TOF spectrometer with a long drift region.

Nab should run first, abBA second.